



CHAIR**Publication number:** WO2005072563**Publication date:** 2005-08-11**Inventor:** HOSOE ISAO (IT); TAKEUCHI HIROSHI (JP); ITO HIROYUKI (JP)**Applicant:** ITOKI CORP (JP); HOSOE ISAO (IT); TAKEUCHI HIROSHI (JP); ITO HIROYUKI (JP)**Classification:****- international:** **A47C1/032; A47C3/026; A47C3/18; A47C3/24; A47C7/40; A47C1/031; A47C3/00; A47C3/02; A47C3/20; A47C7/40;** (IPC1-7): A47C7/54; A47C3/18; A47C3/24**- european:** A47C1/032B; A47C3/026; A47C3/18; A47C3/24; A47C7/40**Application number:** WO2005JP01230 20050128**Priority number(s):** JP20040024178 20040130; JP20040193934 20040630**Cited documents:** JP61159956U
 JP10215978[Report a data error here](#)**Abstract of WO2005072563**

A chair, comprising a leg column (1), a seat (3), and a back support (4). An intermediate support body (9) is fitted to the top end of the leg column (1), the seat (3) and a back frame (5) are fitted to the intermediate support body (9), and the back support (4) is fitted to the top end of the back frame (5) through a joint device (11). The seat (3) is formed in a rectangular shape in plan view, and horizontally swingably mounted on the intermediate support body (9). The back support (4) can be freely rotated about a first axis (13), and freely swung about a second axis (12). Since the seat (3) and the back support (4) can be changed in various attitudes, the chair can be changed in various use modes.

Data supplied from the **esp@cenet** database - Worldwide